

LIEFERPROGRAMM
Stock Program

Aluminium Profile AlMgSi0,5

Flachstangen, Vierkant- u. Rechteckrohre,
Rundrohre, Rundstangen, T-Profile,
U-Profile, Vierkantstangen,
Winkel-Profile, Z-Profile

Verkauf / Office

Tel.: +43(0)6245 / 20362

Fax: +43(0)6245 / 20362-19

Aluminium Flachstangen

Abmessung mm	Gewicht Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
10 x 3	0,081	•	40 x 4	0,432	•	70 x 10	1,890	•
10 x 4	0,108	•	40 x 5	0,540	•	70 x 12	2,268	•
10 x 5	0,135	•	40 x 6	0,648	•	70 x 15	2,835	•
10 x 6	0,162	•	40 x 8	0,864	•	70 x 20	3,780	•
10 x 8	0,216	•	40 x 10	1,080	•	70 x 25	4,725	•
12 x 3	0,097	•	40 x 12	1,296	•	70 x 30	5,670	•
12 x 4	0,130	•	40 x 15	1,620	•	70 x 35	6,615	•
12 x 5	0,162	•	40 x 20	2,160	•	70 x 40	7,560	•
12 x 6	0,194	•	40 x 25	2,700	•	70 x 50	9,450	•
12 x 8	0,259	•	40 x 30	3,240	•	75 x 5	1,103	•
12 x 10	0,324	•	45 x 3	0,365	•	75 x 6	1,215	•
15 x 2	0,081	•	45 x 4	0,486	•	75 x 8	1,620	•
15 x 3	0,122	•	45 x 5	0,608	•	75 x 10	2,025	•
15 x 4	0,162	•	45 x 6	0,729	•	80 x 2	0,432	•
15 x 5	0,203	•	45 x 8	0,972	•	80 x 3	0,648	•
15 x 6	0,243	•	45 x 10	1,215	•	80 x 4	0,864	•
15 x 8	0,324	•	45 x 15	1,823	•	80 x 5	1,080	•
15 x 10	0,405	•	45 x 20	2,430	•	80 x 6	1,296	•
15 x 12	0,486	•	45 x 25	3,038	•	80 x 8	1,728	•
18 x 3	0,146	•	45 x 30	3,645	•	80 x 10	2,160	•
18 x 4	0,194	•	50 x 2	0,270	•	80 x 12	2,592	•
18 x 8	0,389	•	50 x 3	0,405	•	80 x 15	3,240	•
20 x 2	0,108	•	50 x 4	0,540	•	80 x 20	4,320	•
20 x 3	0,162	•	50 x 5	0,675	•	80 x 25	5,400	•
20 x 4	0,216	•	50 x 6	0,810	•	80 x 30	6,480	•
20 x 5	0,270	•	50 x 8	1,080	•	80 x 35	7,560	•
20 x 6	0,324	•	50 x 10	1,350	•	80 x 40	8,640	•
20 x 8	0,432	•	50 x 12	1,620	•	80 x 50	10,800	•
20 x 10	0,540	•	50 x 15	2,025	•	80 x 60	12,960	•
20 x 12	0,648	•	50 x 20	2,700	•	90 x 3	0,729	•
20 x 15	0,810	•	50 x 25	3,375	•	90 x 4	0,972	•
25 x 2	0,135	•	50 x 30	4,050	•	90 x 5	1,215	•
25 x 3	0,203	•	50 x 35	4,725	•	90 x 6	1,458	•
25 x 4	0,270	•	50 x 40	5,400	•	90 x 8	1,944	•
25 x 5	0,338	•	55 x 4	0,594	•	90 x 10	2,430	•
25 x 6	0,405	•	55 x 5	0,743	•	90 x 15	3,645	•
25 x 8	0,540	•	55 x 6	0,891	•	90 x 20	4,860	•
25 x 10	0,675	•	55 x 8	1,188	•	90 x 25	6,075	•
25 x 12	0,810	•	55 x 10	1,485	•	90 x 30	7,290	•
25 x 15	1,013	•	55 x 20	2,970	•	90 x 40	9,720	•
25 x 20	1,350	•	60 x 2	0,324	•	100 x 2	0,540	•
30 x 2	0,162	•	60 x 3	0,468	•	100 x 3	0,810	•
30 x 3	0,243	•	60 x 4	0,648	•	100 x 4	1,080	•
30 x 4	0,324	•	60 x 5	0,810	•	100 x 5	1,350	•
30 x 5	0,405	•	60 x 6	0,972	•	100 x 6	1,620	•
30 x 6	0,486	•	60 x 8	1,296	•	100 x 8	2,160	•
30 x 8	0,648	•	60 x 10	1,620	•	100 x 10	2,700	•
30 x 10	0,810	•	60 x 12	1,944	•	100 x 12	3,240	•
30 x 12	0,972	•	60 x 15	2,430	•	100 x 15	4,050	•
30 x 15	1,215	•	60 x 20	3,240	•	100 x 20	5,400	•
30 x 20	1,620	•	60 x 25	4,050	•	100 x 25	6,750	•
30 x 25	2,025	•	60 x 30	4,860	•	100 x 30	8,100	•
35 x 2	0,189	•	60 x 35	5,670	•	100 x 40	10,800	•
35 x 3	0,284	•	60 x 40	6,480	•	100 x 50	13,500	•
35 x 4	0,378	•	60 x 50	8,100	•	100 x 60	16,200	•
35 x 5	0,473	•	65 x 5	0,878	•	110 x 8	2,376	•
35 x 6	0,567	•	65 x 6	1,053	•	110 x 10	2,970	•
35 x 8	0,756	•	65 x 8	1,404	•	110 x 30	8,910	•
35 x 10	0,945	•	65 x 10	1,755	•	120 x 4	1,296	•
35 x 12	1,134	•	70 x 2	0,378	•	120 x 5	1,620	•
35 x 15	1,418	•	70 x 3	0,567	•	120 x 6	1,944	•
35 x 20	1,890	•	70 x 4	0,756	•	120 x 8	2,592	•
35 x 25	2,363	•	70 x 5	0,945	•	120 x 10	3,240	•
40 x 2	0,216	•	70 x 6	1,134	•	120 x 12	3,888	•
40 x 3	0,324	•	70 x 8	1,512	•	120 x 15	4,860	•

Aluminium Flachstangen

Abmessung mm	Gewicht Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
120 x 20	6,480	•	150 x 3	1,215	•	180 x 15	7,290	•
120 x 30	9,720	•	150 x 5	2,025	•	180 x 20	9,720	•
120 x 40	12,960	•	150 x 8	3,240	•	200 x 5	2,700	•
125 x 10	3,375	•	150 x 10	4,050	•	200 x 8	4,320	•
130 x 5	1,755	•	150 x 12	4,860	•	200 x 10	5,400	•
130 x 8	2,808	•	150 x 15	6,075	•	200 x 15	8,100	•
130 x 10	3,510	•	150 x 20	8,100	•	200 x 20	10,800	•
130 x 15	5,265	•	150 x 30	12,150	•	200 x 30	16,200	•
130 x 20	7,020	•	160 x 10	4,320	•	250 x 8	5,400	•
140 x 5	1,890	•	160 x 15	6,480	•	250 x 10	6,750	•
140 x 10	3,780	•	160 x 20	8,640	•	250 x 20	13,500	•
140 x 15	5,670	•	180 x 5	2,430	•	300 x 10	8,100	•
140 x 20	7,560	•	180 x 10	4,860	•	300 x 20	16,200	•

Ausführung: nach EN 573 -3, 755 -2/-5, gepresst, in Herstellungslängen.

Aluminium Vierkant- und Rechteckrohre

Abmessung H B S mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung H B S mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung H B S mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
15 x 15 x 1,5	0,225	•	40 x 20 x 3,0	0,875	•	60 x 20 x 2,0	0,821	•
15 x 15 x 2,0	0,281	•	40 x 20 x 4,0	1,123	•	60 x 20 x 3,0	1,199	•
20 x 10 x 1,5	0,219	•	40 x 25 x 2,0	0,659	•	60 x 20 x 4,0	1,555	•
20 x 10 x 2,0	0,281	•	40 x 25 x 3,0	0,956	•	60 x 25 x 2,0	0,875	•
20 x 15 x 1,5	0,259	•	40 x 30 x 2,0	0,713	•	60 x 25 x 3,0	1,280	•
20 x 15 x 2,0	0,335	•	40 x 30 x 2,5	0,878	•	60 x 30 x 2,0	0,929	•
20 x 20 x 1,5	0,300	•	40 x 30 x 3,0	1,037	•	60 x 30 x 3,0	1,361	•
20 x 20 x 2,0	0,389	•	40 x 30 x 4,0	1,339	•	60 x 34 x 3,0	1,426	•
20 x 20 x 3,0	0,551	•	40 x 40 x 1,5	0,624	•	60 x 40 x 2,0	1,037	•
25 x 10 x 2,0	0,335	•	40 x 40 x 2,0	0,821	•	60 x 40 x 2,5	1,283	•
25 x 15 x 1,5	0,300	•	40 x 40 x 2,5	1,013	•	60 x 40 x 3,0	1,523	•
25 x 15 x 1,8	0,354	•	40 x 40 x 3,0	1,199	•	60 x 40 x 4,0	1,987	•
25 x 15 x 2,0	0,389	•	40 x 40 x 3,5	1,387	•	60 x 50 x 3,0	1,685	•
25 x 20 x 2,0	0,443	•	40 x 40 x 4,0	1,555	•	60 x 50 x 4,0	2,203	•
25 x 25 x 1,5	0,381	•	40 x 40 x 5,0	1,890	•	60 x 60 x 2,0	1,253	•
25 x 25 x 2,0	0,497	•	42 x 42 x 3,0	1,264	•	60 x 60 x 2,5	1,553	•
25 x 25 x 3,0	0,713	•	45 x 20 x 2,0	0,659	•	60 x 60 x 3,0	1,847	•
30 x 10 x 1,5	0,300	•	45 x 25 x 2,0	0,713	•	60 x 60 x 4,0	2,419	•
30 x 10 x 2,0	0,389	•	45 x 34 x 3,0	1,183	•	60 x 60 x 5,0	2,970	•
30 x 15 x 1,5	0,340	•	45 x 45 x 2,0	0,929	•	65 x 20 x 2,0	0,875	•
30 x 15 x 2,0	0,443	•	50 x 15 x 2,0	0,659	•	65 x 65 x 2,5	1,688	•
30 x 20 x 1,5	0,381	•	50 x 20 x 2,0	0,713	•	70 x 20 x 2,0	0,929	•
30 x 20 x 2,0	0,497	•	50 x 20 x 3,0	1,037	•	70 x 25 x 2,5	1,215	•
30 x 20 x 3,0	0,713	•	50 x 20 x 4,0	1,339	•	70 x 30 x 2,0	1,037	•
30 x 25 x 2,0	0,551	•	50 x 25 x 2,0	0,767	•	70 x 30 x 3,0	1,523	•
30 x 30 x 1,5	0,462	•	50 x 25 x 2,5	0,945	•	70 x 40 x 3,0	1,685	•
30 x 30 x 2,0	0,605	•	50 x 25 x 3,0	1,118	•	70 x 50 x 4,0	2,420	•
30 x 30 x 2,5	0,743	•	50 x 30 x 2,0	0,821	•	70 x 70 x 2,0	1,469	•
30 x 30 x 3,0	0,875	•	50 x 30 x 2,5	1,013	•	70 x 70 x 4,0	2,851	•
34 x 20 x 2,0	0,540	•	50 x 30 x 3,0	1,199	•	75 x 50 x 3,0	1,928	•
34 x 20 x 3,0	0,778	•	50 x 34 x 3,0	1,264	•	80 x 20 x 2,0	1,037	•
34 x 34 x 2,0	0,691	•	50 x 40 x 2,0	0,929	•	80 x 20 x 2,5	1,283	•
34 x 34 x 3,0	1,004	•	50 x 40 x 2,5	1,148	•	80 x 25 x 2,0	1,091	•
35 x 15 x 2,0	0,497	•	50 x 40 x 3,0	1,361	•	80 x 30 x 2,0	1,145	•
35 x 20 x 2,0	0,551	•	50 x 40 x 4,0	1,771	•	80 x 30 x 3,0	1,685	•
35 x 25 x 2,0	0,605	•	50 x 45 x 2,0	0,983	•	80 x 30 x 4,0	2,203	•
35 x 35 x 2,0	0,713	•	50 x 50 x 2,0	1,037	•	80 x 40 x 2,0	1,253	•
35 x 35 x 3,0	1,037	•	50 x 50 x 2,5	1,283	•	80 x 40 x 2,5	1,553	•
40 x 10 x 2,0	0,497	•	50 x 50 x 3,0	1,523	•	80 x 40 x 3,0	1,847	•
40 x 15 x 1,5	0,421	•	50 x 50 x 4,0	1,987	•	80 x 40 x 4,0	2,419	•
40 x 15 x 2,0	0,551	•	50 x 50 x 5,0	2,430	•	80 x 50 x 2,0	1,361	•
40 x 20 x 1,5	0,462	•	55 x 50 x 3,0	1,604	•	80 x 50 x 3,0	2,009	•
40 x 20 x 2,0	0,605	•	55 x 55 x 2,0	1,145	•	80 x 50 x 4,0	2,635	•
40 x 20 x 2,5	0,743	•	56 x 31 x 2,5	1,107	•	80 x 50 x 5,0	3,240	•

Aluminium Vierkant- und Rechteckrohre

Abmessung H B S mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung H B S mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung H B S mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
80 x 60 x 2,5	1,823	•	100 x 100 x 3,0	3,143	•	150 x 30 x 2,8	2,637	•
80 x 60 x 3,0	2,171	•	100 x 100 x 4,0	4,147	•	150 x 40 x 4,0	3,931	•
80 x 60 x 4,0	2,851	•	100 x 100 x 5,0	5,130	•	150 x 50 x 2,0	2,117	•
80 x 80 x 2,0	1,685	•	110 x 50 x 2,5	2,093	•	150 x 50 x 4,0	4,147	•
80 x 80 x 3,0	2,495	•	110 x 60 x 4,0	3,499	•	150 x 60 x 5,0	5,400	•
80 x 80 x 4,0	3,283	•	120 x 20 x 2,0	1,469	•	150 x 100 x 3,0	3,953	•
80 x 80 x 5,0	4,050	•	120 x 30 x 2,0	1,577	•	150 x 150 x 2,5	3,985	•
90 x 40 x 3,0	2,009	•	120 x 30 x 3,0	2,333	•	150 x 150 x 5,0	7,830	•
90 x 90 x 4,0	3,715	•	120 x 40 x 2,0	1,685	•	160 x 40 x 4,0	4,147	•
100 x 18 x 2,0	1,231	•	120 x 40 x 2,5	2,093	•	160 x 60 x 4,0	4,58	•
100 x 20 x 2,0	1,253	•	120 x 40 x 3,0	2,495	•	160 x 80 x 4,0	5,011	•
100 x 25 x 2,0	1,307	•	120 x 40 x 4,0	3,283	•	170 x 25 x 1,8	1,827	•
100 x 30 x 2,0	1,361	•	120 x 50 x 3,0	2,657	•	170 x 25 x 2,0	2,026	•
100 x 30 x 3,0	2,009	•	120 x 50 x 4,0	3,499	•	170 x 70 x 4,0	5,011	•
100 x 40 x 2,0	1,469	•	120 x 60 x 3,0	2,819	•	180 x 40 x 4,0	4,579	•
100 x 40 x 2,5	1,823	•	120 x 60 x 4,0	3,715	•	180 x 50 x 4,0	4,795	•
100 x 40 x 3,0	2,171	•	120 x 80 x 3,0	3,143	•	180 x 60 x 3,0	3,791	•
100 x 40 x 4,0	2,851	•	120 x 120 x 2,5	3,173	•	180 x 80 x 4,0	5,443	•
100 x 50 x 2,0	1,577	•	120 x 120 x 4,0	5,011	•	200 x 18 x 2,0	2,311	•
100 x 50 x 3,0	2,333	•	120 x 120 x 5,0	6,210	•	200 x 30 x 2,8	3,393	•
100 x 50 x 4,0	3,067	•	130 x 30 x 3,0	2,495	•	200 x 50 x 2,5	3,308	•
100 x 50 x 5,0	3,780	•	130 x 50 x 4,0	3,715	•	200 x 50 x 4,0	5,227	•
100 x 60 x 2,0	1,685	•	140 x 20 x 3,0	2,495	•	200 x 60 x 4,0	5,443	•
100 x 60 x 3,0	2,495	•	140 x 40 x 4,0	3,715	•	200 x 80 x 4,0	5,875	•
100 x 60 x 4,0	3,283	•	140 x 60 x 2,5	2,633	•	200 x 100 x 4,0	6,307	•
100 x 60 x 5,0	4,050	•	140 x 60 x 4,0	4,148	•	200 x 100 x 5,0	7,830	•
100 x 80 x 2,5	2,363	•	140 x 80 x 4,0	4,579	•	300 x 120 x 4,5	9,988	•
100 x 80 x 3,0	2,819	•	140 x 80 x 6,0	6,739	•			•
100 x 100 x 2,0	2,117	•	145 x 145 x 3,0	4,601	•			•

Ausführung: nach EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4, gepresst, warm ausgehärtet, in Herstellungslängen.

Aluminium Rundrohre

Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
6 x 1,0	0,042	•	20 x 5,0	0,636	•	35 x 3,0	0,814	•
8 x 1,0	0,059	•	22 x 1,0	0,178	•	35 x 4,0	1,052	•
10 x 1,0	0,076	•	22 x 1,5	0,261	•	35 x 5,0	1,272	•
10 x 1,5	0,108	•	22 x 3,0	0,483	•	38 x 1,5	0,464	•
10 x 2,0	0,136	•	24 x 1,5	0,286	•	38 x 3,0	0,891	•
12 x 1,0	0,093	•	25 x 1,0	0,204	•	40 x 1,5	0,490	•
12 x 1,5	0,134	•	25 x 1,5	0,299	•	40 x 2,0	0,645	•
12 x 2,0	0,170	•	25 x 2,0	0,390	•	40 x 2,5	0,795	•
13 x 3,0	0,254	•	25 x 2,5	0,477	•	40 x 3,0	0,942	•
14 x 2,0	0,204	•	25 x 3,0	0,560	•	40 x 4,0	1,221	•
15 x 1,0	0,119	•	25 x 5,0	0,848	•	40 x 5,0	1,484	•
15 x 1,5	0,172	•	28 x 1,5	0,337	•	40 x 10,0	2,545	•
15 x 2,0	0,221	•	28 x 2,0	0,441	•	42 x 1,5	0,515	•
16 x 1,0	0,127	•	28 x 3,0	0,636	•	42 x 2,0	0,679	•
16 x 1,5	0,184	•	28 x 4,0	0,814	•	42 x 2,5	0,838	•
16 x 2,0	0,238	•	30 x 1,5	0,363	•	42 x 3,0	0,992	•
16 x 2,5	0,286	•	30 x 2,0	0,475	•	42 x 3,5	1,143	•
18 x 1,0	0,144	•	30 x 2,5	0,583	•	42 x 4,0	1,289	•
18 x 1,5	0,210	•	30 x 3,0	0,687	•	45 x 1,5	0,553	•
18 x 2,0	0,271	•	30 x 4,0	0,882	•	45 x 2,0	0,729	•
18 x 3,0	0,382	•	30 x 5,0	1,060	•	45 x 2,5	0,901	•
19 x 1,0	0,153	•	32 x 1,5	0,388	•	45 x 3,0	1,069	•
20 x 1,0	0,161	•	32 x 2,0	0,509	•	45 x 5,0	1,696	•
20 x 1,5	0,235	•	32 x 3,0	0,738	•	46 x 3,0	1,094	•
20 x 2,0	0,305	•	33 x 2,0	0,526	•	48 x 2,5	0,965	•
20 x 2,5	0,371	•	35 x 1,5	0,426	•	48 x 3,0	1,145	•
20 x 3,0	0,433	•	35 x 2,0	0,560	•	48 x 4,0	1,493	•
20 x 4,0	0,543	•	35 x 2,5	0,689	•	50 x 1,5	0,617	•

Aluminium Rundrohre

Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
50 x 2,0	0,814	•	76 x 3,0	1,858	•	120 x 3,0	2,977	•
50 x 2,5	1,007	•	80 x 2,0	1,323	•	120 x 4,0	3,936	•
50 x 3,0	1,196	•	80 x 2,5	1,643	•	120 x 5,0	4,877	•
50 x 4,0	1,561	•	80 x 3,0	1,959	•	120 x 8,0	7,600	•
50 x 5,0	1,909	•	80 x 4,0	2,579	•	125 x 4,0	4,105	•
50 x 10,0	3,393	•	80 x 5,0	3,181	•	125 x 10,0	9,755	•
54 x 2,0	0,882	•	80 x 10,0	5,938	•	130 x 3,0	3,232	•
55 x 2,5	1,113	•	80,4 x 4,5	2,897	•	130 x 5,0	5,301	•
55 x 5,0	2,121	•	84 x 2,0	1,391	•	130 x 15,0	14,632	•
56 x 3,0	1,349	•	85 x 5,0	3,393	•	133 x 3,0	3,308	•
58 x 3,0	1,400	•	86 x 3,0	2,112	•	133 x 4,0	4,409	•
60 x 1,5	0,744	•	90 x 2,0	1,493	•	140 x 4,0	4,614	•
60 x 2,0	0,983	•	90 x 3,0	2,214	•	140 x 5,0	5,726	•
60 x 2,5	1,219	•	90 x 5,0	3,605	•	150 x 3,0	3,741	•
60 x 3,0	1,450	•	90 x 10,0	6,786	•	150 x 5,0	6,150	•
60 x 4,0	1,900	•	100 x 2,0	1,663	•	156 x 3,0	3,893	•
60 x 5,0	2,333	•	100 x 2,5	2,068	•	159 x 4,0	5,259	•
60 x 6,0	2,748	•	100 x 3,0	2,468	•	160 x 4,0	5,293	•
60 x 10,0	4,241	•	100 x 4,0	3,257	•	160 x 5,0	6,574	•
65 x 2,0	1,069	•	100 x 5,0	4,029	•	168 x 3,5	4,884	•
65 x 2,5	1,325	•	100 x 6,0	4,784	•	170 x 5,0	6,998	•
65 x 5,0	2,545	•	100 x 10,0	7,634	•	180 x 5,0	7,422	•
66 x 3,0	1,603	•	105 x 2,5	2,174	•	200 x 5,0	8,270	•
70 x 2,0	1,154	•	106 x 3,0	2,621	•	208 x 4,0	7,492	•
70 x 3,0	1,705	•	108 x 3,0	2,672	•	210 x 5,0	8,694	•
70 x 4,0	2,239	•	108 x 4,0	3,529	•	219 x 4,0	7,815	•
70 x 5,0	2,757	•	110 x 3,0	2,723	•	250 x 5,0	11,486	•
70 x 10,0	5,089	•	110 x 5,0	4,453	•	258 x 4,0	9,903	•
75 x 2,5	1,537	•	110 x 10,0	8,482	•	273 x 4,5	11,398	•
75 x 5,0	2,969	•	114,3 x 3,0	3,029	•	300 x 4,0	11,924	•
76 x 2,5	1,559	•	115 x 5,0	4,665	•	323,9 x 5,5	15,494	•

Ausführung: nach EN 573-3, 755-1/-2/-7/-8/-9, DIN 1748-3/-4, 9107, gepresst, warm ausgehärtet, Herstellungslängen

Aluminium Rundstangen

Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
6	0,076	•	22	1,026	•	65	8,959	•
8	0,136	•	25	1,325	•	70*	10,391	•
10	0,212	•	30	1,909	•	75*	11,928	•
12	0,305	•	35	2,598	•	80*	13,572	•
14	0,416	•	40	3,393	•	90*	17,177	•
15	0,477	•	45	4,294	•	100*	21,206	•
16	0,543	•	50	5,301	•	120*	30,536	•
18	0,687	•	55	6,415	•	150*	47,713	•
20	0,848	•	60	7,643	•			

Ausführung: nach EN 573 -3, 755 -1/ -2/ -3, gepresst, warm ausgehärtet, in Herstellungslängen,
*verschiedene Längen – bitte jeweils anfragen

Aluminium T-Profile

Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
15 x 15 x 2,0	0,151	•	40 x 20 x 2,0	0,313	•	60 x 60 x 4,0	1,253	•
20 x 20 x 2,0	0,205	•	40 x 40 x 2,0	0,421	•	60 x 60 x 6,0	1,847	•
20 x 20 x 3,0	0,300	•	40 x 40 x 3,0	0,624	•	60 x 100 x 5,0	2,093	•
20 x 40 x 2,0	0,313	•	40 x 40 x 4,0	0,821	•	70 x 70 x 5,0	1,823	•
25 x 25 x 2,0	0,259	•	45 x 45 x 3,0	0,701	•	70 x 70 x 8,0	2,851	•
25 x 25 x 3,0	0,389	•	50 x 50 x 4,0	1,037	•	80 x 50 x 5,0	1,688	•
30 x 15 x 2,0	0,232	•	50 x 50 x 5,0	1,283	•	80 x 80 x 4,0	1,685	•
30 x 30 x 2,0	0,313	•	50 x 50 x 6,0	1,523	•	80 x 80 x 6,0	2,495	•
30 x 30 x 3,0	0,462	•	50 x 80 x 5,0	1,688	•	90 x 30 x 2,0	0,637	•
30 x 60 x 4,0	0,929	•	60 x 30 x 4,0	0,929	•	100 x 60 x 5,0	2,093	•
35 x 35 x 2,0	0,367	•	60 x 40 x 4,0	1,037	•	100 x 100 x 10	5,13	•
35 x 35 x 3,0	0,543	•	60 x 40 x 5,0	1,283	•			

Ausführung: nach EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4, DIN 9714, gepresst, warm ausgehärtet, in Herstellungslängen

Aluminium U-Profile

Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
10 x 10 x 2,0	0,140	•	40 x 25 x 2,0	0,464	•	60 x 60 x 5,0	2,295	•
10 x 20 x 2,0	0,248	•	40 x 25 x 3,0	0,680	•	65 x 25 x 2,5	0,743	•
12 x 12 x 1,5	0,134	•	40 x 25 x 4,0	0,886	•	65 x 55 x 2,5	1,148	•
12 x 12 x 2,0	0,173	•	40 x 30 x 2,0	0,518	•	70 x 35 x 3,0	1,085	•
12 x 13 x 2,0	0,184	•	40 x 30 x 3,0	0,761	•	70 x 40 x 3,0	1,166	•
14 x 12 x 2,0	0,184	•	40 x 40 x 2,0	0,626	•	70 x 40 x 4,0	1,534	•
14 x 16 x 2,0	0,227	•	40 x 40 x 2,5	0,776	•	80 x 20 x 2,0	0,626	•
15 x 15 x 2,0	0,221	•	40 x 40 x 3,0	0,923	•	80 x 30 x 3,0	1,085	•
15 x 20 x 1,5	0,211	•	40 x 40 x 4,0	1,210	•	80 x 40 x 3,0	1,247	•
15 x 20 x 2,0	0,275	•	40 x 40 x 5,0	1,485	•	80 x 40 x 4,0	1,642	•
16 x 13 x 1,5	0,158	•	40 x 50 x 2,0	0,734	•	80 x 40 x 5,0	2,025	•
20 x 10 x 2,0	0,194	•	40 x 60 x 4,0	1,642	•	80 x 40 x 6,0	2,398	•
20 x 15 x 2,0	0,248	•	40 x 65 x 2,0	0,896	•	80 x 45 x 3,0	1,328	•
20 x 20 x 1,5	0,231	•	45 x 25 x 3,0	0,721	•	80 x 45 x 6,0	2,560	•
20 x 20 x 2,0	0,302	•	45,5 x 12 x 2,5	0,435	•	80 x 50 x 3,0	1,409	•
20 x 20 x 3,0	0,437	•	50 x 15 x 2,0	0,410	•	80 x 50 x 5,0	2,295	•
20 x 25 x 2,0	0,356	•	50 x 20 x 2,0	0,464	•	80 x 60 x 5,0	2,565	•
20 x 30 x 2,0	0,410	•	50 x 20 x 3,0	0,680	•	80 x 80 x 4,0	2,506	•
20 x 40 x 2,0	0,518	•	50 x 25 x 2,0	0,518	•	86 x 40 x 3,0	1,296	•
20 x 40 x 2,5	0,641	•	50 x 25 x 2,5	0,641	•	90 x 20 x 2,5	0,844	•
25 x 15 x 2,0	0,275	•	50 x 30 x 2,0	0,572	•	90 x 40 x 3,0	1,328	•
25 x 20 x 2,0	0,329	•	50 x 30 x 3,0	0,842	•	90 x 50 x 3,0	1,490	•
25 x 20 x 3,0	0,478	•	50 x 30 x 4,0	1,102	•	90 x 50 x 5,0	2,430	•
25 x 25 x 2,0	0,383	•	50 x 40 x 3,0	1,004	•	100 x 20 x 2,0	0,743	•
25 x 25 x 3,0	0,559	•	50 x 40 x 4,0	1,318	•	100 x 40 x 3,0	1,409	•
25 x 40 x 2,0	0,545	•	50 x 50 x 2,0	0,788	•	100 x 50 x 3,0	1,571	•
30 x 15 x 2,0	0,302	•	50 x 50 x 3,0	1,166	•	100 x 50 x 5,0	2,565	•
30 x 15 x 3,0	0,437	•	50 x 50 x 4,0	1,534	•	100 x 50 x 10,0	4,860	•
30 x 20 x 2,0	0,356	•	50 x 50 x 5,0	1,890	•	100 x 70 x 6,0	3,694	•
30 x 20 x 3,0	0,518	•	55 x 45 x 2,0	0,761	•	106 x 40 x 3,0	1,458	•
30 x 30 x 2,0	0,464	•	55 x 50 x 2,0	0,815	•	110 x 40 x 3,0	1,490	•
30 x 30 x 3,0	0,680	•	60 x 20 x 2,0	0,518	•	120 x 20 x 2,5	1,046	•
30 x 40 x 3,0	0,842	•	60 x 25 x 2,5	0,709	•	120 x 40 x 3,0	1,571	•
30 x 50 x 3,0	1,004	•	60 x 25 x 3,0	0,842	•	120 x 60 x 5,0	3,105	•
30 x 60 x 2,0	0,788	•	60 x 30 x 3,0	0,923	•	120 x 60 x 8,0	4,838	•
35 x 20 x 2,0	0,383	•	60 x 40 x 2,5	0,911	•	140 x 40 x 3,0	1,733	•
35 x 25 x 2,0	0,437	•	60 x 40 x 3,0	1,085	•	140 x 40 x 6,0	3,370	•
35 x 35 x 2,0	0,545	•	60 x 40 x 4,0	1,426	•	140 x 60 x 6,0	4,018	•
35 x 35 x 3,0	0,802	•	60 x 40 x 5,0	1,755	•	150 x 30 x 4,0	2,182	•
35 x 53,5 x 3,5	1,276	•	60 x 50 x 2,0	0,842	•	150 x 37 x 3,0	1,766	•
40 x 15 x 2,0	0,356	•	60 x 50 x 2,5	1,046	•	160 x 80 x 8,0	6,566	•
40 x 20 x 2,0	0,410	•	60 x 50 x 3,0	1,247	•	200 x 40 x 3,0	2,219	•
40 x 20 x 2,5	0,506	•	60 x 60 x 3,0	1,409	•	220 x 20 x 4,0	2,722	•
40 x 20 x 3,0	0,599	•	60 x 60 x 4,0	1,858	•	260 x 38 x 3,0	2,673	•

Aluminium Vierkantstangen

Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gewicht t Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
6 x 6	0,097	•	18 x 18	0,875	•	50 x 50	6,750	•
8 x 8	0,173	•	20 x 20	1,080	•	55 x 55	8,168	•
10 x 10	0,270	•	25 x 25	1,688	•	60 x 60	9,720	•
12 x 12	0,389	•	30 x 30	2,430	•	70 x 70	13,230	•
14 x 14	0,529	•	35 x 35	3,308	•	80 x 80	17,280	•
15 x 15	0,608	•	40 x 40	4,320	•	100 x 100	27,000	•
16 x 16	0,691	•	45 x 45	5,468	•			

Ausführung: nach EN 573 -3, 755 -1/ -2/ -4, gepresst, warm ausgehärtet, in Herstellungslängen

Aluminium Winkel-Profile

Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
10 x 10 x 2,0	0,097	•	35 x 15 x 2,5	0,321	•	50 x 25 x 2,5	0,489	•
12 x 12 x 2,0	0,119	•	35 x 20 x 2,0	0,286	•	50 x 25 x 3,0	0,583	•
15 x 10 x 1,5	0,095	•	35 x 20 x 3,0	0,421	•	50 x 25 x 4,0	0,767	•
15 x 10 x 2,0	0,124	•	35 x 25 x 2,0	0,313	•	50 x 25 x 5,0	0,945	•
15 x 15 x 1,5	0,115	•	35 x 25 x 3,0	0,462	•	50 x 30 x 2,0	0,421	•
15 x 15 x 2,0	0,151	•	35 x 30 x 3,0	0,502	•	50 x 30 x 3,0	0,624	•
15 x 15 x 3,0	0,219	•	35 x 35 x 2,0	0,367	•	50 x 30 x 4,0	0,821	•
20 x 10 x 1,5	0,115	•	35 x 35 x 3,0	0,543	•	50 x 30 x 5,0	1,013	•
20 x 10 x 2,0	0,151	•	35 x 35 x 4,0	0,713	•	50 x 35 x 4,0	0,875	•
20 x 10 x 3,0	0,219	•	35 x 35 x 5,0	0,878	•	50 x 40 x 2,0	0,475	•
20 x 15 x 2,0	0,178	•	40 x 10 x 2,0	0,259	•	50 x 40 x 3,0	0,705	•
20 x 15 x 2,5	0,219	•	40 x 15 x 2,0	0,286	•	50 x 40 x 4,0	0,929	•
20 x 15 x 3,0	0,259	•	40 x 15 x 4,0	0,551	•	50 x 40 x 5,0	1,148	•
20 x 20 x 1,5	0,156	•	40 x 20 x 2,0	0,313	•	50 x 50 x 2,0	0,529	•
20 x 20 x 2,0	0,205	•	40 x 20 x 2,5	0,388	•	50 x 50 x 3,0	0,786	•
20 x 20 x 2,5	0,253	•	40 x 20 x 3,0	0,462	•	50 x 50 x 4,0	1,037	•
20 x 20 x 3,0	0,300	•	40 x 20 x 4,0	0,605	•	50 x 50 x 5,0	1,283	•
20 x 20 x 4,0	0,389	•	40 x 20 x 5,0	0,743	•	50 x 50 x 6,0	1,523	•
25 x 10 x 2,0	0,178	•	40 x 25 x 2,0	0,340	•	50 x 50 x 8,0	1,987	•
25 x 10 x 2,5	0,219	•	40 x 25 x 2,5	0,422	•	50 x 50 x 10,0	2,430	•
25 x 15 x 2,0	0,205	•	40 x 25 x 3,0	0,502	•	60 x 10 x 2,0	0,367	•
25 x 15 x 2,5	0,253	•	40 x 25 x 4,0	0,659	•	60 x 15 x 2,0	0,394	•
25 x 15 x 3,0	0,300	•	40 x 30 x 2,0	0,367	•	60 x 20 x 2,0	0,421	•
25 x 20 x 1,5	0,176	•	40 x 30 x 2,5	0,456	•	60 x 20 x 2,5	0,523	•
25 x 20 x 2,0	0,232	•	40 x 30 x 3,0	0,543	•	60 x 20 x 3,0	0,624	•
25 x 20 x 2,5	0,287	•	40 x 30 x 4,0	0,713	•	60 x 25 x 2,0	0,448	•
25 x 20 x 3,0	0,340	•	40 x 40 x 2,0	0,421	•	60 x 25 x 2,5	0,557	•
25 x 25 x 2,0	0,259	•	40 x 40 x 3,0	0,624	•	60 x 25 x 3,0	0,664	•
25 x 25 x 2,5	0,321	•	40 x 40 x 4,0	0,821	•	60 x 25 x 4,0	0,875	•
25 x 25 x 3,0	0,381	•	40 x 40 x 5,0	1,013	•	60 x 30 x 2,0	0,475	•
25 x 25 x 4,0	0,497	•	45 x 10 x 2,0	0,286	•	60 x 30 x 3,0	0,705	•
30 x 10 x 1,5	0,156	•	45 x 15 x 2,0	0,313	•	60 x 30 x 4,0	0,929	•
30 x 10 x 2,0	0,205	•	45 x 20 x 2,0	0,340	•	60 x 30 x 5,0	1,148	•
30 x 15 x 2,0	0,232	•	45 x 20 x 3,0	0,502	•	60 x 40 x 2,0	0,529	•
30 x 15 x 3,0	0,340	•	45 x 25 x 2,0	0,367	•	60 x 40 x 3,0	0,786	•
30 x 20 x 1,5	0,196	•	45 x 30 x 3,0	0,583	•	60 x 40 x 4,0	1,037	•
30 x 20 x 2,0	0,259	•	45 x 45 x 2,0	0,475	•	60 x 40 x 5,0	1,283	•
30 x 20 x 2,5	0,321	•	45 x 45 x 3,0	0,705	•	60 x 40 x 6,0	1,523	•
30 x 20 x 3,0	0,381	•	45 x 45 x 4,0	0,929	•	60 x 50 x 2,0	0,583	•
30 x 20 x 4,0	0,497	•	45 x 45 x 5,0	1,148	•	60 x 60 x 2,0	0,637	•
30 x 25 x 2,0	0,286	•	50 x 10 x 2,0	0,313	•	60 x 60 x 2,5	0,793	•
30 x 25 x 3,0	0,421	•	50 x 15 x 2,0	0,340	•	60 x 60 x 3,0	0,948	•
30 x 30 x 2,0	0,313	•	50 x 15 x 2,5	0,422	•	60 x 60 x 4,0	1,253	•
30 x 30 x 2,5	0,388	•	50 x 15 x 3,0	0,502	•	60 x 60 x 5,0	1,553	•
30 x 30 x 3,0	0,462	•	50 x 20 x 2,0	0,367	•	60 x 60 x 6,0	1,847	•
30 x 30 x 4,0	0,605	•	50 x 20 x 2,5	0,456	•	60 x 60 x 8,0	2,419	•
30 x 30 x 5,0	0,743	•	50 x 20 x 3,0	0,543	•	60 x 60 x 10,0	2,970	•
35 x 10 x 2,0	0,232	•	50 x 20 x 4,0	0,713	•	65 x 15 x 2,0	0,421	•
35 x 15 x 2,0	0,259	•	50 x 25 x 2,0	0,394	•	70 x 15 x 2,0	0,448	•

Aluminium Winkel-Profile

Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
70 x 20 x 2,0	0,475	•	80 x 80 x 6,0	2,495	•	120 x 20 x 2,5	0,928	•
70 x 25 x 2,0	0,502	•	80 x 80 x 8,0	3,283	•	120 x 40 x 4,0	1,685	•
70 x 25 x 2,5	0,624	•	80 x 80 x 10,0	4,050	•	120 x 50 x 5,0	2,228	•
70 x 30 x 2,0	0,529	•	90 x 40 x 4,0	1,361	•	120 x 60 x 2,0	0,961	•
70 x 30 x 3,0	0,786	•	90 x 90 x 3,0	1,434	•	120 x 60 x 6,0	2,819	•
70 x 40 x 2,0	0,583	•	90 x 90 x 10,0	4,590	•	120 x 60 x 8,0	3,715	•
70 x 40 x 4,0	1,145	•	100 x 20 x 2,0	0,637	•	120 x 80 x 3,0	1,596	•
70 x 50 x 5,0	1,553	•	100 x 25 x 2,0	0,664	•	120 x 80 x 6,0	3,143	•
70 x 70 x 2,5	0,928	•	100 x 30 x 3,0	1,029	•	120 x 80 x 8,0	4,147	•
70 x 70 x 5,0	1,823	•	100 x 40 x 2,0	0,745	•	120 x 80 x 10,0	5,130	•
70 x 70 x 6,0	2,171	•	100 x 40 x 3,0	1,110	•	120 x 100 x 4,0	2,333	•
70 x 70 x 7,0	2,514	•	100 x 40 x 4,0	1,469	•	120 x 120 x 2,5	1,603	•
75 x 50 x 5,0	1,620	•	100 x 50 x 2,0	0,799	•	120 x 120 x 8,0	5,011	•
80 x 15 x 2,0	0,502	•	100 x 50 x 3,0	1,191	•	120 x 120 x 10,0	6,210	•
80 x 20 x 2,0	0,529	•	100 x 50 x 4,0	1,577	•	120 x 120 x 12,0	7,387	•
80 x 25 x 2,0	0,556	•	100 x 50 x 5,0	1,958	•	130 x 30 x 3,0	1,272	•
80 x 25 x 2,5	0,692	•	100 x 50 x 6,0	2,333	•	130 x 80 x 6,0	3,305	•
80 x 30 x 3,0	0,867	•	100 x 50 x 8,0	3,067	•	140 x 40 x 3,0	1,434	•
80 x 40 x 2,0	0,637	•	100 x 50 x 10,0	3,780	•	140 x 40 x 6,0	2,819	•
80 x 40 x 3,0	0,948	•	100 x 60 x 6,0	2,495	•	150 x 50 x 4,0	2,117	•
80 x 40 x 4,0	1,253	•	100 x 60 x 8,0	3,283	•	150 x 75 x 8,0	4,687	•
80 x 40 x 5,0	1,553	•	100 x 70 x 2,0	0,907	•	150 x 80 x 6,0	3,629	•
80 x 40 x 6,0	1,847	•	100 x 75 x 8,0	3,607	•	150 x 100 x 5,0	3,308	•
80 x 50 x 3,0	1,029	•	100 x 80 x 4,0	1,901	•	150 x 100 x 10,0	6,480	•
80 x 50 x 4,0	1,361	•	100 x 80 x 6,0	2,819	•	160 x 40 x 2,6	1,386	•
80 x 50 x 5,0	1,688	•	100 x 80 x 8,0	3,715	•	160 x 40 x 4,0	2,117	•
80 x 60 x 4,0	1,469	•	100 x 100 x 4,0	2,117	•	160 x 60 x 8,0	4,579	•
80 x 60 x 6,0	2,171	•	100 x 100 x 5,0	2,633	•	180 x 80 x 10,0	6,750	•
80 x 80 x 2,0	0,853	•	100 x 100 x 6,0	3,143	•	180 x 150 x 6,0	5,249	•
80 x 80 x 3,0	1,272	•	100 x 100 x 8,0	4,147	•	200 x 100 x 10,0	7,830	•
80 x 80 x 4,0	1,685	•	100 x 100 x 10,0	5,130	•	200 x 100 x 15,0	11,54	•
80 x 80 x 5,0	2,093	•	110 x 30 x 2,0	0,745	•	230 x 100 x 3,0	2,649	•

Ausführung: nach EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4, DIN 1771, gepresst, warm ausgehärtet, in Herstellungslängen

Aluminium Z-Profile

Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66	Abmessung mm	Gew. Kg / m	AlMgSi0,5 F22 EN AW-6060 T66
10 x 15 x 10 x 2,0	0,194	•	40 x 40 x 40 x 3,0	0,923	•
15 x 15 x 15 x 2,0	0,221	•	43 x 18 x 18 x 3,0	0,591	•
18 x 20 x 21 x 3,0	0,429	•	50 x 18 x 18 x 3,0	0,648	•
20 x 18 x 21 x 3,0	0,429	•	50 x 30 x 30 x 3,0	0,842	•
20 x 20 x 20 x 2,0	0,302	•	50 x 35 x 35 x 3,0	0,923	•
25 x 17 x 17 x 2,0	0,279	•	50 x 50 x 50 x 4,0	1,534	•
25 x 25 x 25 x 3,0	0,559	•	60 x 24 x 24 x 2,0	0,562	•
30 x 25 x 25 x 3,0	0,599	•	60 x 24 x 24 x 4,0	1,080	•
30 x 30 x 30 x 3,0	0,680	•	60 x 30 x 30 x 2,0	0,626	•
30 x 30 x 40 x 3,0	0,761	•	60 x 40 x 40 x 4,0	1,426	•
32 x 17 x 17 x 2,0	0,335	•	70 x 40 x 40 x 3,0	1,166	•
40 x 15 x 15 x 2,0	0,356	•	86 x 40 x 40 x 3,0	1,296	•
40 x 30 x 30 x 3,0	0,761	•			

Ausführung: nach EN 573 -3, 755 -1/ -2/ -9, DIN 1748 -4, gepresst, warm ausgehärtet, in Herstellungslängen



BRANDNER Metalle

Brandner Metalle GmbH

Adnet 115b
A-5421 Adnet

Tel.: +43(0)6245 / 20362
Fax: +43(0)6245 / 20362-19

E-Mail: br.metalle@sbg.at

